



# Specifications

■ Standard
  Optional
N/A Not Applicable

|                         | Low Profile Bucket, 50" | Low Profile Bucket - 56" | Low Profile Bucket - 62" | Low Profile Bucket - 68" | Low Profile Bucket - 74" | Low Profile Bucket - 80" |
|-------------------------|-------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|
| <b>General</b>          |                         |                          |                          |                          |                          |                          |
| <b>Operating Weight</b> | 171 kg                  | 194 kg                   | 219 kg                   | 234 kg                   | 242 kg                   | 266 kg                   |
| <b>Length</b>           | 902 mm                  | 902 mm                   | 902 mm                   | 902 mm                   | 902 mm                   | 902 mm                   |
| <b>Width</b>            | 1270 mm                 | 1422 mm                  | 1575 mm                  | 1727 mm                  | 1880 mm                  | 2032 mm                  |
| <b>Height</b>           | 546 mm                  | 546 mm                   | 546 mm                   | 546 mm                   | 546 mm                   | 546 mm                   |
| <b>Number of Teeth</b>  | 6 Bolt-on               | 6 Bolt-on                | 7 Bolt-on                | 7 Bolt-on                | 8 Bolt-on                | 8 Bolt-on                |

|                            | Low Profile Bucket, 50" | Low Profile Bucket - 56" | Low Profile Bucket - 62" | Low Profile Bucket - 68" | Low Profile Bucket - 74" | Low Profile Bucket - 80" |
|----------------------------|-------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|
| <b>Bucket Specs</b>        |                         |                          |                          |                          |                          |                          |
| <b>ISO Heaped Capacity</b> | 0.33 m <sup>3</sup>     | 0.37 m <sup>3</sup>      | 0.41 m <sup>3</sup>      | 0.45 m <sup>3</sup>      | 0.5 m <sup>3</sup>       | 0.54 m <sup>3</sup>      |
| <b>ISO Struck Capacity</b> | 0.26 m <sup>3</sup>     | 0.28 m <sup>3</sup>      | 0.3 m <sup>3</sup>       | 0.34 m <sup>3</sup>      | 0.37 m <sup>3</sup>      | 0.4 m <sup>3</sup>       |
| <b>Predrilled For</b>      | Bolt-on Edges or Teeth  | Bolt-on Edges or Teeth   | Bolt-on Edges or Teeth   | Bolt-on Edges or Teeth   | Bolt-on Edges or Teeth   | Bolt-on Edges or Teeth   |

| Compatible Carriers |  |   |   |   |   |   |
|---------------------|--|---|---|---|---|---|
| Skid-Steer Loaders  |  |   |   |   |   |   |
| Bobcat A770         |  |   |   |   | ■ | ■ |
| Bobcat S450         |  | ■ | ■ | ■ |   |   |
| Bobcat S510         |  |   | ■ | ■ | ■ |   |
| Bobcat S530         |  |   | ■ | ■ | ■ |   |
| Bobcat S550         |  |   | ■ | ■ | ■ |   |
| Bobcat S570         |  |   | ■ | ■ | ■ |   |
| Bobcat S590         |  |   | ■ | ■ | ■ |   |
| Bobcat S595         |  |   | ■ | ■ | ■ |   |
| Bobcat S630         |  |   |   | ■ | ■ | ■ |
| Bobcat S650         |  |   |   | ■ | ■ | ■ |
| Bobcat S740         |  |   |   | ■ | ■ | ■ |
| Bobcat S750         |  |   |   | ■ | ■ | ■ |
| Bobcat S770         |  |   |   | ■ | ■ | ■ |

| Compact Track Loaders |  |   |   |   |   |   |
|-----------------------|--|---|---|---|---|---|
| Bobcat T450           |  | ■ | ■ | ■ |   |   |
| Bobcat T550           |  |   |   | ■ | ■ |   |
| Bobcat T590           |  |   |   | ■ | ■ |   |
| Bobcat T595           |  |   |   | ■ | ■ |   |
| Bobcat T630           |  |   |   |   | ■ | ■ |
| Bobcat T650           |  |   |   |   | ■ | ■ |

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.