



■ Standard   
  Optional   
 N/A Not Applicable

**Rotary Tiller - 40"**

**Rotary Tiller - 62"**

**Rotary Tiller - 76"**

⊖ **General**

	Rotary Tiller - 40"	Rotary Tiller - 62"	Rotary Tiller - 76"
<b>Operating Weight</b>	215 kg	299 kg	340 kg
<b>Length</b>	836 mm	n/a	n/a
<b>Width</b>	1217 mm	1798 mm	2144 mm
<b>Height</b>	615 mm	n/a	n/a
<b>Working Depth</b>	6" Maximum	6" Maximum	6" Maximum
<b>Drive</b>	Direct Drive	Direct Drive	Direct Drive
<b>Tine Rotation</b>	Bi-rotational	Bi-rotational	Bi-rotational
<b>Working Width</b>	1031 mm	1577 mm	1915 mm
<b>Travel Direction</b>	Forward/Reverse	Forward/Reverse	Forward/Reverse
<b>Tines</b>	28	36	44
<b>Flow Range Min</b>	34,1 l/min	64,4 l/min	64,4 l/min
<b>Flow Range Max</b>	68,1 l/min	151,4 l/min	151,4 l/min

⊖ **Compatible Carriers**

<b>Skid-Steer Loaders</b>			
Bobcat A770			■
Bobcat S70	■		
Bobcat S450		■	
Bobcat S510		■	■
Bobcat S530		■	■
Bobcat S550		■	■
Bobcat S570		■	■
Bobcat S590		■	■
Bobcat S595		■	■
Bobcat S630		■	■
Bobcat S650		■	■
Bobcat S740		■	■
Bobcat S750		■	■
Bobcat S770		■	■

<b>Compact Track Loaders</b>			
Bobcat T450		■	
Bobcat T550		■	■
Bobcat T590		■	■
Bobcat T595		■	■
Bobcat T630		■	■
Bobcat T650		■	■
Bobcat T740			■
Bobcat T750			■
Bobcat T770			■

<b>Mini Track Loaders</b>			
Bobcat MT52	■		
Bobcat MT55	■		
Bobcat MT85	■		

<b>Toolcat™ Work Machine</b>			
Bobcat 5600		■	■
Bobcat 5610		■	■

<b>Telehandler</b>			
Bobcat V417			■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.