



Bobcat®

ATTACHMENT PLANER




One Tough Animal.

PLANER - SPECIFICATIONS

Description

Equipped with direct-drive, high-torque hydraulic motor. These low maintenance attachments efficiently mill asphalt or concrete. Planers feature hydraulic side-shift for planing close to walls and curbs. Consistent depth control and ski depth visible from the operator's seat. Make precise adjustments with fingertip controls.

Requirements



Planer: Includes hydraulic depth adjust, hydraulic sideshift and hoses. Loader must be equipped with an attachment control kit.

Performance

Teeth life: 20 - 50 hours
Drum life: 200 - 400 hours
Production rate: 40 - 50 m²/h

* Performances are estimated only and can vary depending on the type of concrete, depth of use, operator experience, ...

Features & Benefits

- Top access panel – for easier bit service and maintenance.
- Side cutting bits – to decrease drum binding in the cut and to produce a vertical edge for improving the joint bond between a new layer of asphalt and the existing layer.
- Hydraulic side-shift – for planing close to walls and curbs, and to easily reposition the drum for another pass.
- Oscillating planer housing – for planing sloping surfaces or to match two uneven surfaces.
- Rear frame wheels – to provide support and reduce tyre bounce while planing.
- Direct-drive high torque motors – for low maintenance and high efficiency.
- Bob-Tach™ mounting system with quick-connect controls – for fast, easy attachment changes.

Specifications

	Planer, 35 cm	Planer, 46 cm	Planer, 61 cm	Planer, 102 cm
Operating weight	502 kg (w/o drum)	540 kg (w/o drum)	569 kg (w/o drum)	1043 kg (w/ drum)
Overall length	1206 mm	1206 mm	1206 mm	1118 mm
Standard drum cutting width	356 mm	457 mm	610 mm	1016 mm
Cutting depth	152 mm	152 mm	152 mm	127 mm
Max. cutting angle	±15 deg.	±15 deg.	±15 deg.	±8 deg. (Hydraulic)
Side-shift (hydraulic)	757 mm	757 mm	757 mm	650 mm
Planing distance (Next to curb, if loader width is less than:)	Flush 1915 mm	Flush 1915 mm	Flush 2042 mm	65 mm
Approved drums	64-356 mm	64-457 mm	64-610 mm	1016 mm

Approved machines: Skid-Steer Loader, Compact Track Loader


Compatibility Charts

	Skid Steer Loaders													Compact Track Loaders							
	S16	S18	S70	S100	S450	S510	S530	S550/H	S570/H	S590/H	S630/H	S650/H	S770/H	S850/H	MT55	T450	T590/H	T650/H	T770/H	T870/H	
Planer, 35 cm (Equipped with 35 cm all purpose drum)					X	X	X	X	X	X	X	X	X			X	X	X	X		
Planer, 46 cm (Equipped with 46 cm fast cut drum)							X	X	X	X	X	X	X				X	X	X	X	
① Planer, 46 cm (Without drum)							X	X	X	X	X	X	X				X	X	X	X	
Planer, 61 cm (Equipped with 61 cm fast cut drum)								X	X	X	X	X	X				X	X	X	X	
Planer, 61 cm (Without drum)								X	X	X	X	X	X				X	X	X	X	
Note: 7-pin attachment control kit is installed as standard on high flow (h) machines.																					
② 7-pin attachment control kit					X	X	X	X	X	X	X	X	X			X	X	X	X	X	



Bobcat is a Doosan company.

Doosan is a global leader in construction equipment, power and water solutions, engines, and engineering proudly serving customers and communities for more than a century. | Bobcat and the Bobcat logo are registered trademarks of Bobcat Company in the United States and various other countries.
©2020 Bobcat Company. All rights reserved.



Bobcat®

Doosan Bobcat Korea Co., Ltd.

www.bobcat.com