



Specifications

■ Standard
 Optional
N/A Not Applicable

General

	HCE20	Hydraulic Clamp, Standard Arm - E26	Hydraulic Clamp, E32, E35 - Standard Arm	Hydraulic Clamp, E42, E45 - Standard Arm	Hydraulic Clamp, E42 - Standard Arm Class III	Hydraulic Clamp, E50 - Standard Arm	Hydraulic Clamp, E60	Hydraulic Clamp, E80	Pro Clamp, Standard Arm, Class III - E32/E35	Pro Clamp, E42, E45 - Standard Arm
Operating Weight	23 kg	57 kg	57 kg	99 kg	78kg	99 kg	145 kg	204 kg	141 kg	241 kg
Length	505 mm	696 mm	696 mm	813 mm	691 mm	813 mm	1092 mm	1118mm	n/a	n/a
Width	n/a	330 mm	330 mm	378 mm	366 mm	378 mm	425 mm	419 mm	340 mm	n/a
Height	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Clamp Width	138 mm	330 mm	330 mm	378 mm	366 mm	378 mm	425 mm	419 mm	340 mm	404 mm
Tooth Radius	503 mm	691 mm	692 mm	813 mm	691 mm	813 mm	820 mm	1041 mm	n/a	n/a
Tooth Thickness	13 mm	19 mm	19 mm	25 mm	19 mm	25 mm	25 mm	25 mm	n/a	n/a

Compatible Carriers

Compact Excavators										
Bobcat E20	■									
Bobcat E26		■								
Bobcat E32			■						■	
Bobcat E32i			■						■	
Bobcat E35			■						■	
Bobcat E35i			■						■	
Bobcat E42				■	■					■
Bobcat E45				■						■
Bobcat E50						■				
Bobcat E63							■			
Bobcat E85								■		

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.