



# Specifications

■ Standard
  Optional
N/A Not Applicable

## General

	<b>Roto Man Platform, Rotating, with hydraulic extension, 300 kg, 240 x 420, carrier with remote control</b>	<b>Roto Rotating Man Platform, 120 x 240 cm with hydraulic extension up to 420 cm. Capacity 800 kg incl. 3 persons for vehicle w/Radio C with proportional distributor</b>	<b>Roto Rotating Man Platform with hydraulic extension, 300 kg, 240 x 420, carrier with remote control, for MB bracket</b>	<b>Roto Rotating Man Platform with hydraulic extension, 300 kg, 240 x 420, with remote control</b>
<b>Platform Dimension</b>	120 x 240 cm	120 x 240 cm	120 x 240 cm	120 x 240 cm
<b>Capacity</b>	300 kg	800 kg	300 kg	300 kg
<b>Maximum Persons</b>	3	3	3	3
<b>Rotation</b>	Yes	Yes	Yes	Yes
<b>Expandable</b>	Up to 420 cm	Up to 420 cm	Up to 420 cm	Up to 600 cm
<b>Weight</b>	780 kg	985 kg	685 kg	1165 kg
<b>Carrier Configuration</b>	Remote control is required	For vehicle w/Radio C with proportional distributor	Remote control is required	Remote control is required
<b>Working Flow</b>	Standard	Standard	Standard	Standard
<b>First Use Installation Time</b>	None	None	None	None

## Compatible Carriers

Rotary Telescopic Handlers				
Bobcat TR38160 EVO	■	■		
Bobcat TR40250 EVO	■	■	■ *	■
Bobcat TR50190 EVO	■	■		■
Bobcat TR50210 EVO	■	■	■ *	■

\* For machine with engine Stage IIIb ONLY

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.