



Specifications

■ Standard
 Optional
 N/A Not Applicable

Vibratory Roller, Padded Drum - 48"
 Vibratory Roller, Smooth Drum - 48"
 Vibratory Roller, Padded Drum - 73"
 Vibratory Roller, Smooth Drum - 73"
 Vibratory Roller, Smooth Drum - 80"

⊖ **General**

Operating Weight	806 kg	811 kg	993 kg	1002 kg	1052 kg
Length	968 mm	968 mm	963 mm	963 mm	963 mm
Width	1537 mm	1537 mm	2007 mm	2007 mm	2184 mm
Height	645 mm	660 mm	645 mm	660 mm	660 mm
Drum Width	1219 mm	1219 mm	1854 mm	1854 mm	2032 mm
Covers Right Side Tires On	66" wide loaders	66" wide loaders	73" wide loaders	73" wide loaders	80" wide loaders
Drum Offset	9" to right	9" to right	Centered	Centered	Centered
Drum Oscillation	+/- 12 degrees	+/- 12 degrees	+/- 7.5 degrees	+/- 7.5 degrees	+/- 7.5 degrees
Dynamic Force	10,519 lbs. @ 17 gpm 14,244 lbs. @ 20 gpm	10,519 lbs @ 17 gpm, 14,244 lbs @ 20 gpm	9,905 lbs. @ 20 gpm, 13,100 lbs. @ 23 gpm	9,905 lbs. @ 20 gpm, 13,100 lbs. @ 23 gpm	9,905 lbs. @ 20 gpm, 13,100 lbs. @ 23 gpm
Frequency	2,448 vpm @ 17 gpm 2,879 vpm @ 20 gpm	2,448 vpm @ 17 gpm, 2,879 vpm @ 20 gpm	2,401 vpm @ 20 gpm, 2,761 vpm @ 23 gpm	2,401 vpm @ 20 gpm, 2,761 vpm @ 23 gpm	2,401 vpm @ 20 gpm, 2,761 vpm @ 23 gpm
Number of Pads	78	n/a	102	n/a	n/a
Drum Diameter (Padded)	645 mm	660 mm	645 mm	660 mm	660 mm
Drum Diameter (Smooth)	n/a	660 mm	n/a	660 mm	660 mm

⊖ **Compatible Carriers**

Skid-Steer Loaders					
Bobcat A770			■	■	■
Bobcat S450	■	■			
Bobcat S510	■	■			
Bobcat S530	■	■			
Bobcat S550	■	■	■	■	
Bobcat S570	■	■	■	■	
Bobcat S590	■	■	■	■	
Bobcat S595	■	■	■	■	
Bobcat S630			■	■	
Bobcat S650			■	■	■
Bobcat S740			■	■	■
Bobcat S750			■	■	■
Bobcat S770			■	■	■
Bobcat S850			■	■	■

Compact Track Loaders					
Bobcat T450	■	■			
Bobcat T550	■	■	■	■	
Bobcat T590	■	■	■	■	
Bobcat T595	■	■	■	■	
Bobcat T630			■	■	■
Bobcat T650			■	■	■
Bobcat T740			■	■	■
Bobcat T750			■	■	■
Bobcat T770			■	■	■
Bobcat T870			■	■	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.