



Specifications

■ Standard
 Optional
 N/A Not Applicable

	Stump Grinder, SG 30	Stump Grinder, SG 60	Stump Grinder, SGX 60
General			
Operating Weight	209 kg	445 kg	451 kg
Length	1175 mm	1143 mm	1143 mm
Width	914 mm	1671 mm	1671 mm
Height	851 mm	1509 mm	1509 mm
Number of Teeth	16	32	32
Grinder Reach At Ground Level	1175 mm	1880 mm	1880 mm
Maximum Cutting Arc	90°	80°	80°
Maximum Cutting Depth	279 mm	381 mm	381 mm
Maximum Cutting Height	279 mm	813 mm	813 mm
Wheel Diameter	457 mm	686 mm	686 mm
Tip Speed	3109-4691 ft./min. (948-1430 m./min.)	4480-6330 ft./min. (1366-1990m./min.)	3321-5511 ft./min. (1012-1680 m./min.)
Transport Width	914 mm	1181 mm	1676 mm

Compatible Carriers

Skid-Steer Loaders			
Bobcat A770		■	■
Bobcat S70	■		
Bobcat S510		■	
Bobcat S530		■	
Bobcat S550		■	■
Bobcat S570		■	■
Bobcat S590		■	■
Bobcat S595		■	■
Bobcat S630		■	■
Bobcat S650		■	■
Bobcat S740		■	■
Bobcat S750		■	■
Bobcat S770		■	■
Bobcat S850		■	■

Compact Track Loaders			
Bobcat T550		■	■
Bobcat T590		■	■
Bobcat T595		■	■
Bobcat T630		■	■
Bobcat T650		■	■
Bobcat T740		■	■
Bobcat T750		■	■
Bobcat T770		■	■
Bobcat T870		■	■

Mini Track Loaders			
Bobcat MT52	■		
Bobcat MT55	■		
Bobcat MT85	■		

Toolcat™ Work Machine			
Bobcat 5600		■	
Bobcat 5610		■	

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.